

Series No.	Engine Code	Cyl. No.	Position	Size (mm)			Shape	Material	Surface treatment	Reference
				d1(D)	h1(B)	a1(T)				

DAEWOO

1	3EA F6B S-TEC I 0.8L YSE	4	1st	68.50	1.20	2.60	BF-IB	SR	Cr/Ox	12140-78B00 94581409
			2nd		1.50	2.80	T1	CR	Fe	
			Oil		2.80	3.00	NIFF-H	SR	Cr/Fe	
2	3EA F6B S-TEC I 0.8L YSE	4	1st	68.50	1.20	2.60	BF-IB	SR	Cr/Ox	12140-78B00 94581409
			2nd		1.47	2.80	TUC	CR	Fe	
			Oil		2.80	2.50	NIFF-S	SR	GN	
3	NP960	4	1st	76.50	1.50	2.80	BF-IB	SR	Cr/Ox	
			2nd		1.50	3.20	TUN	CR	Fe	
			Oil		3.00	2.90	NIFF-S	SR	Cr/Fe	
4	D2366	6	1st	123.00	3.35 (3.20)	5.00	BF-K1	HB	Cr/Ox	65.02503-8236(cy1)
			2nd		3.00	5.00	T1-IC	HB	Cr/Fe	
			Oil		4.00	2.35 (3.90)	BC16-S	SR	GN	
5	2848T	6	1st	128.00	3.35 (3.105)	5.10	BF-K1	HB	Out. Cr	65.02503-8252(cy1)
			2nd		3.00	5.30	T1-RC	CR	Out. Cr	
			Oil		4.00	2.40 (4.00)	BC16-S	SR	GN	