Series		Cyl. No.	Position	Size (mm)			Shono	Material	Surface	Reference
No.				d1(D)	h1(B)	a1(T)	Shape	Material	treatment	Reference
DAF										
1	DAF 620(1700/1900)	4	1st	104.18	2.85 (2.605)	4.30	BF-K1	НВ	Out. Cr	
			2nd		2.50	4.30	T1-IB	CR	Out. Cr	
			Oil		4.00	3.10 (4.20)	E-BC16	CR	Out. Cr	
2	DAF 825(2100-2500)	6	1st	118.00	3.35 (3.105)	4.90	BF-K1	НВ	Out. Cr	
			2nd		3.00	5.00	T1	CR	Out. Cr	
			3rd		3.00	5.00	T1	CR	W	
			Oil		6.00	3.60 (5.25)	E-BC16	CR	Out. Cr	
3	DAF 75(RS180/200/22 2)	6	1st	118.00	3.35 (3.105)	4.90	BF-K1	НВ	Out. Cr	
			2nd		3.00	5.00	T1	CR	W	
			Oil		4.00	3.20 (4.10)	E-BC16	CR	Out. Cr	
4	DAF1160	6	1st	- 130.00	3.10 (2.985)	5.30	BF-K1	НВ	Out. Cr	
			2nd		3.15	5.40	T1	CR	Out. Cr	
			3rd		3.15	5.40	T1	CR	Out. Cr	
			Oil		6.35	3.70 (5.30)	E-BC16	CR	Out. Cr	
5	DAF CF85/XF105	6	1st	130.00	2.85 (2.605)	4.75	BF-K1-IB	SR	CCIP	
			2nd		2.50	4.60	T1-RB	F14	Fe	
			Oil		3.00	3.00 (4.20)	E-BC16	CR	CCIP	
6	DAF 85CF/CF85/95XF/ XF95	6	1st	130.00	3.95 (3.832)	5.30	BF-K1	НВ	CCIP	
			2nd		3.15	5.00	T1	CR	Fe	
			Oil		4.00	3.50 (4.50)	E-BC16	CR	Out. Cr	
7	DAF 95	6	1st	130.00	3.95 (3.832)	5.30	BF-K1	НВ	Out. Cr	
			2nd		3.16	5.30	T1	CR	Out. Cr	
			Oil		4.00	3.50 (4.60)	E-BC16	CR	Out. Cr	

Series	Series No. Engine Code	Cyl. No.	Position	Size (mm)		Shape	Material	Surface	Reference	
No.				d1(D)	h1(B)	a1(T)	Snape	Material	treatment	Kelelelice
DAF										
			1st		3.85 (3.605)	5.40	BF-K1-IB	НВ	CCIP	
8	DAF CF85/XF105	6	2nd	130.00	3.15	5.20	T1	CR	Fe	
			Oil		4.00	3.40 (4.55)	E-BC16	CR	Cr/Fe	