Series No.	Engine Code	Cyl. No.	Position	Size (mm)			Shana	Motorial	Surface	Reference
				d1(D)	h1(B)	a1(T)	Shape	Material	treatment	Reference
MACK										
1	E7	6	1st	123.83	3.10 (2.628)	4.75	BF-K1	НВ	МО	
			2nd		2.40	4.75	T1-IB	НВ	Cr/Fe	
			Oil		4.75	3.20 (5.15)	E-BC16	CR	In. and Out. Cr	
2	E7	6	1st	123.83	3.00 (2.623)	4.75	BF-K1	НВ	CCIP	
			2nd		2.40	4.75	T1-IB	НВ	Cr/Fe	
			Oil		4.75	3.20 (5.15)	E-BC16	CR	Cr/Fe	
3	E7	6	1st	123.83	3.00 (2.73)	4.75	BF-K1	НВ	МО	
			2nd		2.40	4.75	T1-IB	НВ	Cr/Fe	
			Oil		4.75	3.20 (5.15)	E-BC16	CR	In. and Out. Cr	
4	E6	6	1st	- 123.83	3.10 (2.628)	4.75	BF-K1	НВ	МО	
			2nd		3.10 (2.628)	4.75	BF-K1	НВ	МО	
			3rd		2.93 (2.55)	4.75	T1-K1-IB	НВ	Out. Cr	
			Oil		4.75	3.25 (5.15)	E-BC16	CR	In. and Out. Cr	
5	E6	6	1st	123.83	3.00 (2.623)	4.75	BF-K1	НВ	CCIP	
			2nd		3.00 (2.623)	4.75	BF-K1	НВ	CCIP	
			3rd		2.93 (2.55)	4.75	T1-K1-IB	НВ	Cr/Fe	
			Oil		4.75	3.20 (5.15)	E-BC16	CR	Cr/Fe	